

## M18 CHX-O | M18 FUEL™ 4-mode SDS-plus hammer with FIXTEC chuck

Article: 4933447420



- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power.
- Fuel gauge displays remaining charge.
- Compatible with M18 CDEX dust extractor.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Second hardest hitting SDS hammer in its class. Powerful hammer mechanism delivers 2.5 J of impact energy at low 8.9 m/s<sup>2</sup> vibrations.

|  | M18 CHX-0  |
|--|------------|
| Article Number   | 4933447420 |
| Battery pack capacity (Ah)                                       | -          |
| Battery type   | Li-ion     |
| Blow energy (EPTA)(J)  | 2.5        |
| Charger supplied   | -          |
| Max. drilling concrete (mm)                                      | 26         |
| Max. drilling steel (mm)   | 13         |
| Max. drilling wood (mm)  | 30         |
| Max. percussion rate (bpm)                                       | 0 - 4900   |
| No load speed (rpm)  | 0 - 1400   |
| No. of batteries supplied  | 0          |
| Optimised drilling capacity in concrete (mm)                     | ø 6 - 20   |
| Sound power level (dB(A))  | 101.7      |
| Sound power level uncertainty (dB(A))                            | 3          |
| Sound pressure level (dB(A))                                     | 90.7       |
| Sound pressure level uncertainty (dB(A))                         | 3          |
| Supplied in  | -          |
| Vibration chiseling (m/s <sup>2</sup> )                          | 9.5        |
| Vibration chiselling uncertainty (m/s <sup>2</sup> )             | 1.5        |
| Vibration drilling (m/s <sup>2</sup> )                           | 8.9        |
| Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ] | 1.5        |
| Voltage (V)  | 18         |
| Weight with battery pack (kg)                                    | -          |