

M18 FID2-0X | M18 Fuel™ 1/4" Hex Impact Driver



- Higher power efficiency under load - outstanding torque of 226 Nm.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 1/4" Hex chuck for quick and easy bit change.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extreme compact design - total length of just 117 mm for access into tight spaces.

	M18 FID2-0X
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	1200/3400/4300/0-4300
Max. bolt diameter	M16
Max. fastening torque (Nm)	226
Max. torque (Nm)	119/176/226/0-226
No load speed (rpm)	1900/2800/3600/0-3600
No. of batteries supplied	0
Sound power level measured (dB(A))	107.75
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	96.75
Sound pressure level uncertainty (dB(A))	3
Supplied in	HD Box
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s ²]	18.63
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s ²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	-