

GENERATOR SPECIFICATION

| | |
|---------------------------|-----------------------------|
| Voltage | 230/115 |
| Phase | 1 |
| Frequency | 50Hz |
| Prime Power (PRP) | 4.0kVA / 3.2kW |
| Alternator | NSM K100F |
| Alternator Type | Brushless - Smooth Waveform |
| Fuel tank capacity | 13.0 Litres |
| Autonomy 75% load | 13.0 Hours |
| LWA | 96 |
| dBa @ 7M | 71 |

ENGINE SPECIFICATION

| | |
|----------------------------|----------------------|
| Engine | Lombardini 15LD 350S |
| Emissions certified | N/A |
| Cylinders | Single |
| Distribution | O.H.V. |
| Aspiration | Normally aspirated |
| Cooling | Air |
| Displacement | 349 cm ³ |
| Rpm | 3000 |
| Starting system | Recoil |
| Fuel | Diesel |



| DIMENSIONS (mm) | | | WEIGHT (KG) |
|-----------------|-------|--------|-------------|
| Length | Width | Height | |
| 775 | 475 | 560 | 84 |



CONTROL BOX

- 1 x 16A & 1 x 32A 115V BS4343 sockets.
- 1 x 16A 230V BS4343 socket.
- Reset circuit breaker overload protection.

STANDARD FEATURES

- Long run fuel tank.
- Easy carry fold-away handles.
- Brushless smooth waveform alternator.

OPTIONS

- Single voltage.
- Electric start (SE4000DLES)
- Trolley kit.

POWER DEFINITION

Prime Power (PRP) :

Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1.